

# SEROIL WPS

## SPECIAL FATS



### Specifications:

**Chemical composition:** Greasing fat polymer.

**Appearance:** Viscous liquid.

**Color:** White.

**Transparency:** Opalescent.

**pH:** 6,5±0,5

**Active Matter:** 51±2

**Charge:** Anionic

### General Properties of product family:

Several special fatliquors range for special Applications/articles.  
Having diverse chemical composition.

### Product properties:

Waterproofing fatliquor. Medium level. Recommended for soft articles, like gloves, garments, nappa. To be used like single fat.

Waterproofing application:

It is recommended do not use any surfactant during the process and make a strong neutralisation, not lower than pH 4,8. To be used like single fat. The maximum effect is achieved after fixation of fat at the end of process with a metallic salt (Cr, Al, Zr).

It can be used like a touch agent.

### Guidance dosages:

General waterproofing (% on shaved weight):

- After Neutralization prior retanning: 3-8%
- In fresh fatliquor bath: 5-10 %
- Like a touch agent together or after fatliquoring : 0,5-2%

Quimser complies with the European standards.

All data and recommendations herein are accurate at the time of publication. QUIMSER S.A. reserves the right to modify them without notice. Work conditions and type of raw material can effect the final results. It is the responsibility of the user to apply the recommendations to the actual conditions and particular purpose.