Quimser S.A.
Leather Chemical Products
www.quimser.com
+34 938 032 688
info@quimser.com
C/Lleida, 39
08711 Òdena, Barcelona (Spain)

SERCRYL PU-301

RESINAS POLIURETANO

Especificaciones:

Composición química:

Resina poliuretano, emulsificantes, agua y aditivos.

Aspecto:

Líquido fluido.

Color:

Blanco.

pH:

7,5±0,5

% Materia activa

33±2%

Solidez a la luz:

Excelente

Carga:

Aniónico

Tiempo de vida:

Debidamente almacenados (+5 Y +35ºC) tienen una duración mínima de 6 meses.

Propiedades generales:

PU estándar de uso general usado para capas de fondo. Para todo tipo de artículos. Excelentes propiedades de grabado a plancha.

Dosis de aplicación:

Las dosis varian según el tipo de acabado requerido. Usualmente usar entre 100-150 g/L

Quimser complies with the European standards.
All data and recommendations herein are accurate at the time of publication. QUIMSER S.A. reserves the right to modify them without notice. Work conditions and type of raw material can effect the final results. It is the responsibility of the user to apply the recommendations to the actual conditions and particular purpose.

www.quimser.com
+34 938 032 688
info@quimser.com
C/Lleida, 39
08711 Òdena, Barcelona (Spain)