Quimser S.A.
Leather Chemical Products
www.quimser.com
+34 938 032 688
info@quimser.com
C/Lleida, 39
08711 Òdena, Barcelona (Spain)

SERLAC TC-333

RESINAS ESPECIALES

Especificaciones:

Composición química:

Resina poliuretano, emulsificantes, agua y aditivos.

Aspecto:

Líquido fluido

Color:

Marfil.

pH:

8,0±0,5

% Materia activa

11±1

Solidez a la luz:

Excelente

Carga:

Aniónico

Tiempo de vida:

Debidamente almacenados (+5 Y +35ºC) tienen una duración mínima de 6 meses.

Propiedades generales:

Producto en base acuosa que sirve como el perfecto sustituto de lacas nitro de uso universal.
Con unos buenos frotes y unas excelentes solideces (y sin amarillear) es una buena opción para proteger cualquier acabado otorgando además un tacto cálido y sedoso.
Aporta buen brillo y buenas propiedades de planchado.

Dosis de aplicación:

La dosis varia en función del grado de brillo requerido. Normalmente usar entre 300-500 g/L en capas finales.

Quimser complies with the European standards.
All data and recommendations herein are accurate at the time of publication. QUIMSER S.A. reserves the right to modify them without notice. Work conditions and type of raw material can effect the final results. It is the responsibility of the user to apply the recommendations to the actual conditions and particular purpose.